

# KIM-66A High-Precision Fiber Cleaver



## Features

- Dedicated for Single fiber cleaving
- Simple and single-step operation
- Blade lift up to 48,000 cleaves
- Compact and light weight
- Equipped with fiber scrap collector



**Kimtech**

COMMUNICATIONS

3.0 μm fiber holder groove

900μm fiber holder groove

250μm fiber holder groove

Padestal

Large platen

Rubber presser foot

Blade

Slider



drop cable



3.0mm Patch cord



0.9mm pigtail

Detail display



**Metal magnet**

It is not easy to crack and deform



**Elastic pressure pad design**

The clamp can be pressed to make the optical fiber not deviate

# Specification

MODEL	KIM – 66A
<i>Applicable Fiber</i>	Single Fiber
<i>Fiber Type</i>	0.25 / 0.9 / 3.0mm Optical fiber
<i>Coating Diameter</i>	125 μm
<i>Cleaved Length</i>	9-24 mm
<i>Cleaved Angle</i>	Average 0.5°
<i>Blade Lift</i>	48,000 cleaves
<i>Operate Mode</i>	Semi-automatic
<i>Dimension(WxDxH)</i>	94mmx75mmx61mm (3.7"x2.95"x2.4")
<i>Weight</i>	360g