

## OUTDOOR WALL MOUNTS

---



### Description

Outdoor Wall-Mount Fiber distribution box made of steel sheet 1.5 mm and powder coated 65 micron. Outdoor Wall Mount is available for 12, 24, 60, 120 fiber in the standard beige color., the cable insertion the distributor is pre-punched for PG 21 cable glands optionally, cable can also be insert with connectors. The cable can be held in the preformed holes by a section cable inlet or cable feed through grommet depending on cable diameter.

### Features / Benefits

- Provides easy access for connector FC ,SC ,LC, E2000 panel
- One door lockable
- IP 65 protected
- 2 splice tray holder

Material : steel or stainless 1.5 mm.

Bracket : 2 mm

Size: MM.

12 - 24 PORT = 120 (D) x 400 (H) x 350 (W)

60 PORT = 154 (D) x 420 (H) x 380 (W)

Material : Aluminum 2 mm.

120 PORT = 195 (D) x 500 (H) x 450 (W)

## OUTDOOR WALL MOUNTS

### SPLICE PROTECTIVE SLEEVE



Splice sleeve for fiber-optic fusion splices can be used to rebuild the primary coating for fiber to provide protection at the fusion joint area.

Structure : Shrinkable sleeve  
Stainless steel rod



#### Generis Specifications :

Description	Typical diameter after heating $\Phi$ (mm)	Fusion Tube $\Phi$ (mm)	Length of the stainless steel rod l(mm)	Length of Sleeve l(mm)
45 mm	2.5	1.3	40	45
60 mm	2.5	1.3	55	60

Change of temperature	Temperature Cycle  Cycles 1 cycle		- 40°C to +85°C  10 cycles 6 hr.
-----------------------	--	--	---